



Firesafe ECO Fire-Rated LED Downlight




Fire rated energy efficient integrated LED downlight.

- 30, 60 & 90 minute fire rated Fully compliant and certified to BS476 Parts 21 and 22
- 3000K warm white and 4000K cool white colour options
- Includes 3x finishes, white fixed base plus Chrome and Brushed Steel magnetic quick change bezels
- Colour rendering index Ra≥80
- Long life 35,000 hours maintenance free operation
- IP65 rated
- Supplied with Easy-fit connector
- Constructed from die-cast aluminium
- Dimmable DuoDimTM Technology compatible with both leading and trailing edge dimmers*
- Instant full light

Product Code	Watts (W)	Volts (V)	Colour Appearance	Colour Temp (K)	Useful Lumens (Im)	Total Lumens (lm)	Beam Angle	Dimensions (mm)			Order Qty
								Dia	Н	Cutout ø	
Single Carton											
11274	6	240	Warm White	3000	520	560	40°	84	72	60-75	1
11281	6	240	Cool White	4000	540	590	40°	84	72	60-75	1

Supplied with pre-wired easy fit connector. Installation may require advice from a qualified person. Part L Compliant of UK Building Regulations. Part B Compliant BS476 Parts 21 and 22. Suitable for 30 minute 600mm/15mm single layer Standard Wallboard, 60 minute 600mm/12.5mm twin layer Fireboard and 90 minute 450mm/15mm twin layer Fireboard ceilings.

* This product is compatible with most dimmer switches, please refer to next page for up-to-date list of compatible dimmer switches.

















Lighting brilliance since 1878

140 YEARS

Phoebe LEDTM is a trading name of Crompton Lamps Limited
Crompton Lamps Limited registered in England and Wales No. 05590551
Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE