




LED MINI LINK-LIGHT



LED Mini Link-Lights

Contents: 1x Mini Link-Light, 2x Mounting Brackets, 2x End Caps, 1x Clear Joint

Code	Wattage	Product Name	Length	Width	Height	Lumen	Colour Temperature	Life	CRI	Qty
4894	2.5W	LED Mini Link-Light	150mm	18mm	8mm	195lm	3000K Warm White	40,000 hrs	≥82	5
4900	5W	LED Mini Link-Light	300mm	18mm	8mm	325lm	3000K Warm White	40,000 hrs	≥82	5
4917	9W	LED Mini Link-Light	600mm	18mm	8mm	590lm	3000K Warm White	40,000 hrs	≥82	5
4924	15W	LED Mini Link-Light	1000mm	18mm	8mm	975lm	3000K Warm White	40,000 hrs	≥82	5
4931	2.5W	LED Mini Link-Light	150mm	18mm	8mm	195m	4000K Cool White	40,000 hrs	≥82	5
4948	5W	LED Mini Link-Light	300mm	18mm	8mm	325m	4000K Cool White	40,000 hrs	≥82	5
4955	9W	LED Mini Link-Light	600mm	18mm	8mm	590m	4000K Cool White	40,000 hrs	≥82	5
4962	15W	LED Mini Link-Light	1000mm	18mm	8mm	975m	4000K Cool White	40,000 hrs	≥82	5



LED Mini Link-Light Power Supplies

Contents: 1x Driver, 1x Touch Sensitive On/Off Switch, 2x 3M Adhesive Strips

Code	Accessory Name	Qty
4979	18W LED Mini Link-Light Driver & On/Off Switch	2
4986	36W LED Mini Link-Light Driver & On/Off Switch	2
4993	60W LED Mini Link-Light Driver & On/Off Switch	2
5006	120W LED Mini Link-Light Driver & On/Off Switch	2



LED Mini Link-Light Accessories

Code	Accessory Name	Length	Qty
5068	4-Way Adapter Lead Split the power supply for up-to 4 separate circuits	500mm	5
5044	Additional Power Lead Connects a power supply directly to a link-light (no switch)	500mm	5
5051	Link Lead (Male-to-Male) Flexibly connect a link-light to a link-light	500mm	5
5648	Link Lead (Female-to-Male) Flexibly connect a switch to a link-light	500mm	3
5075	2-Way Connector Left	20mm	10
5082	2-Way Connector Right	20mm	10
5099	3-Way Connector T-Shaped	20mm	5
5105	4-Way Connector	20mm	10
5112	Internal Corner Connector	12mm	10
5129	Replacement Mounting Brackets		10
5136	45° Angled Mounting Brackets		10



LED Mini Link-Light Switches

Code	Accessory Name	Length	Qty
5013	Additional Touch Sensitive On/Off	67mm	5
5020	Touch Sensitive Dimmer	67mm	5
5037	Motion Sensor On/Off	67mm	5



Phoebe Mini Link-Light products must be installed by a qualified electrician. IP20 rated not suitable for outdoor use.

WARM
WHITE

COOL
WHITE

Phoebe LED™ is a trading name of Crompton Lamps Limited registered in England and Wales No. 05590551
Registered office and correspondence address: Unit 2, Martree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@phoebeled.com Web: www.phoebeled.com

All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. © Crompton Lamps Limited 2018.



LED MINI LINK-LIGHT

Point-of-Sale Merchandise



Products feature Eurohook Packaging



Interactive Mini Link-Light Display Board with Flyer Holder



Customer Flyers



Slot Wall Foam Header Card

LED Mini Link-Lights Point-of-Sale Merchandise

Code	Name
4891	Slot Wall Foam Header Card (800mm x 300mm)
4892	Interactive Mini Link-Light Display Board with Flyer Holder (400mm x 300mm)
4893	Customer Flyers Refill (Pack of 50)

Call the sales team on 01274 657 088 for details on how to order

Lighting brilliance since 1878



Phoebe LED™ is a trading name of Crompton Lamps Limited registered in England and Wales No. 05590551
Registered office and correspondence address: Unit 2, Martree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@phoebeled.com Web: www.phoebeled.com

All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. © Crompton Lamps Limited 2018.