

**PHOEBE
LED**



LED MINI LINK-LIGHT

Ultra-Slim Concealed Lighting For Your Home

**BE YOUR OWN
LIGHTING
DESIGNER**



CHOOSE YOUR
COLOUR &
LENGTHS



LED Mini Link-Lights

Contents: 1x Mini Link-Light, 2x Mounting Brackets, 2x End Caps, 1x Clear Joint

Code	Wattage	Product Name	Length	Width	Height	Lumen	Colour Temperature	Life	CRI	Price
4894	2.5W	LED Mini Link-Light	150mm	18mm	8mm	195lm	3000K Warm White	40,000 hrs	≥82	
4900	5W	LED Mini Link-Light	300mm	18mm	8mm	325lm	3000K Warm White	40,000 hrs	≥82	
4917	9W	LED Mini Link-Light	600mm	18mm	8mm	590lm	3000K Warm White	40,000 hrs	≥82	
4924	15W	LED Mini Link-Light	1000mm	18mm	8mm	975lm	3000K Warm White	40,000 hrs	≥82	
4931	2.5W	LED Mini Link-Light	150mm	18mm	8mm	195m	4000K Cool White	40,000 hrs	≥82	
4948	5W	LED Mini Link-Light	300mm	18mm	8mm	325m	4000K Cool White	40,000 hrs	≥82	
4955	9W	LED Mini Link-Light	600mm	18mm	8mm	590m	4000K Cool White	40,000 hrs	≥82	
4962	15W	LED Mini Link-Light	1000mm	18mm	8mm	975m	4000K Cool White	40,000 hrs	≥82	

CHOOSE YOUR
POWER
SUPPLY



LED Mini Link-Light Power Supplies

Contents: 1x Driver, 1x Touch Sensitive On/Off Switch, 2x 3M Adhesive Strips

Code	Accessory Name	Price
4979	18W LED Mini Link-Light Driver & On/Off Switch	
4986	36W LED Mini Link-Light Driver & On/Off Switch	
4993	60W LED Mini Link-Light Driver & On/Off Switch	
5006	120W LED Mini Link-Light Driver & On/Off Switch	

CHOOSE YOUR
CONNECTORS &
ACCESSORIES



LED Mini Link-Light Accessories

Code	Accessory Name	Length	Price
5068	4-Way Adapter Lead Split the power supply for up-to 4 separate circuits	500mm	
5044	Additional Power Lead Connects a power supply directly to a link-light (no switch)	500mm	
5051	Link Lead (Male-to-Male) Flexibly connect a link-light to a link-light	500mm	
5648	Link Lead (Female-to-Male) Flexibly connect a switch to a link-light	500mm	
5075	2-Way Connector Left	20mm	
5082	2-Way Connector Right	20mm	
5099	3-Way Connector T-Shaped	20mm	
5105	4-Way Connector	20mm	
5112	Internal Corner Connector	12mm	
5129	Replacement Mounting Brackets		
5136	45° Angled Mounting Brackets		

CHOOSE YOUR
SWITCH



LED Mini Link-Light Switches

Code	Accessory Name	Length	Price
5013	Additional Touch Sensitive On/Off	67mm	
5020	Touch Sensitive Dimmer	67mm	
5037	Motion Sensor On/Off	67mm	



Phoebe Mini Link-Light products must be installed by a qualified electrician.
IP20 rated not suitable for outdoor use.

WARM
WHITE

COOL
WHITE

Experts in lighting since 1878