


Technical Information RESAFE MAR 8.5W Smart Firesafe All-in-One Fire-Rated LED Downlight Ο 30, 60 and 90 minute fire-rated 0000000000 App and voice control Custom lighting schemes Control smart lights from anywhere Scheduled smart lighting н Smart dimmable and aroup liahtina 2700K-6500K tuneable white

- IP65 rated
- 50.000 hour life
- 100,000 switching cycles
- 60° beam angle



89 5

Product Code	Watts (W)	Volts (V)	Colour Appearance	Colour Temp (K)	Useful Total Lumens Lumens (Im) (Im)	ens Angle	Dimensions (mm)			Order Qty	
					()	()		Dia	Н	Cutout ø	
Single Carton											
12851	8.5	240	Tuneable White	2700-6500	650	700	60°	89	65	70-72	1

12646-10	Optional Chrome Bezel - 10 Pack	
12040-10	Ophonal Chiome bezer - To Tack	

Installation may require advice from a qualified person. Part L Compliant of UK Building Regulations. Part B Compliant BS476 Parts 21 and 22. Suitable for 30 minute 600mm/15mm single layer Standard Wallboard, 60 minute 600mm/12.5mm twin layer Fireboard and 90 minute 450mm/15mm twin laver Fireboard ceilings.



Crompton Lamps Limited registered in England and Wales No: 05590551

Crompton Lamps Limited Marrtree Business Park **Bowling Back Lane** Bradford BD4 80E

Tel: 01274 657 088 Fax: 01274 657 087 Email: sales@cromptonlamps.com



Design and production by Marketing, Crompton Lamps Limited E. & O. E. © Crompton Lamps Limited 2019. All rights reserved.

www.cromptonlamps.com in