



LED PAR38 Dimmable




LED PAR (Pressed Aluminium Reflector) lamps feature a glass enclosure and highly reflective aluminium coating applied internally.

- 25,000 hour life
- 12,500 switching cycles
- ES-E27 cap
- Colour rendering index Ra≥80
- Prismatic lens
- DuoDim™ Technology compatible with both leading and trailing edge dimmers*
- IP65 rated for outdoor wet weather use

Product Code	Watts (W)	Volts (V)	Cap	Colour Appearance		Lumens	Lumens	Equiv.		Dimensions (mm)		Energy Rating	
					(K)	(lm)	(lm)	(W)		Dia	Н		
PAR30 Dimmable*- Single Carton													
12745	18	240	ES-E27	Warm White	3000	1400	1700	120	45°	131	122	A ⁺	1

^{*} The lamp is compatible with most dimmer switches, please refer to website for up-to-date list of compatible dimmer switches.













Lighting brilliance since 1878



Crompton Lamps Limited registered in England and Wales No. 05590551
Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE
Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com



Dimmer Compatibility



LED PAR38 Dimmable Part Codes: 12745



The below table is designed to help you choose a suitable dimmer switch for your Crompton Lamp dimmable product. Crompton Lamps have extensively tested the below dimmer switches to evaluate their dimming function and to make sure the dimmer switch meets our dimming compatibility standards.

All compatible dimmer switches may require low end trimming.

For guidelines on dimmer switches not listed below, or for more information please contact Crompton Lamps.

Manufacturer	Dimmer Model	Dimmer Dimmer Wattage Type		Lamps Tested Per Circuit	Notes	
Click	MD9014	100W	Dual Mode	1-5	Dims 0%-100%	
Click	MD9042	60W-400W	Leading	1-2	Dims 50%-100%	
Hamilton	741XLEDITB100	5W-100W	Dual Mode	1-5	Dims 10%-100%	
Hamilton	GRID100LED	5W-100W	Dual Mode	1-5	Steps from 10%-100%	
MK	K1523WHILV	40W-300W	Leading	1-3	Dims 40%-95%	
Zano	ZMC250	5W-250W	LED	1-5	Dims 0%-95%	
Varilight	V-Pro JQP401W	10W-400W	Trailing	1-5	Dims 5%-100%	
Varilight	V-Pro JQP252W	10W-250W	Trailing	1-5	Dims 5%-100%	

Lighting brilliance since 1878

