

# Single Ended Pulse Start Metal Halide Tubular



Metal halide lamps give a white light and have high colour rendering ability. Tubular clear lamps are more commonly used in floodlighting applications.

- Metal halide lamps require enclosure with cover glass
- Up to 20,000 hour life
- $\pm 75^\circ$  horizontal operating position
- GES-E40 cap

| Product Code                       | Watts (W) | Operating Position | Cap     | Colour Rendering Index/Group | Colour Temp (K) | Circuit Type | Total Lumens (lm) | Average Rated Life (hrs) | Energy Rating | Order Qty |
|------------------------------------|-----------|--------------------|---------|------------------------------|-----------------|--------------|-------------------|--------------------------|---------------|-----------|
| <b>Tubular Clear Single Carton</b> |           |                    |         |                              |                 |              |                   |                          |               |           |
| MHT250XPS4K                        | 250       | $\pm 75^\circ$     | GES-E40 | 20                           | 4500            | Pulse        | 22000             | 10000                    | A             | 12        |
| MHT400XPS4K                        | 400       | $\pm 75^\circ$     | GES-E40 | 20                           | 4200            | Pulse        | 40000             | 20000                    | A+            | 12        |



| Watts (W) | Dimensions (mm) |     |
|-----------|-----------------|-----|
|           | Dia             | H   |
| 250       | 46              | 256 |
| 400       | 46              | 281 |



GES-E40 Cap



Lighting brilliance since 1878

