

**PHOEBE
LED**



Spectrum LED Downlight with Bluetooth App Control



Spectrum Orion downlight does not have an ambient rim light

Mains operated fire rated IP65 energy efficient integrated LED downlight, with tuneable white spotlight and RGB/white colour changing ambient halolight

- Twin light outputs can be used together or independently - 9417/9424 only
- Download the Phoebe LED Spectrum control app from Google Play or Apple App Store
- Fully dimmable spotlight tuneable from 2200K extra warm white to 6500K daylight colour temperature
- 30, 60 & 90 minute fire rated - Fully compliant and certified to BS476 Parts 21 and 22*
- Full spectrum RGB/White dimmable halolight with selectable colour or fast/slow cycle through colours options - 9417/9424 only
- Supplied with a toolless loop-in/loop-out quick connector.
- Colour rendering index Ra≥80
- Long life 50,000 hours maintenance free operation
- 100,000 switching cycles
- IP65 rated, suitable for outdoor use
- Instant full light





Each Spectrum downlight is supplied with white, chrome and brushed aluminium bezels with magnetic fastener for quick removal/change



Gloss Black and Antique Brass Bezels now available

| Product Code | Description | Watts (W) | Volts (V) | Colour Appearance Inner/Outer | Colour Temp (K) | Useful Lumens (lm) | Beam Angle | Dimensions (mm) Dia H Cutout ø | Order Qty |
|----------------------------------|---------------------|-----------|-----------|-------------------------------|-----------------|--------------------|------------|--------------------------------|-----------|
| Single Carton | | | | | | | | | |
| 9417 | RGB Halo | 10 | 240 | CCT/RGB | 2200-6500 | 650 | 40° | 80 55 67-70 | 1 |
| 9424 | White Halo | 10 | 240 | CCT/CCT | 2200-6500 | 650 | 40° | 80 55 67-70 | 1 |
| 10475 | Orion | 10 | 240 | CCT/ - | 2200-6500 | 650 | 40° | 80 53 67-70 | 1 |
| Accessories Single Carton | | | | | | | | | |
| 10505 | Gloss Black Bezel | | | | | | | 80 | 1 |
| 10512 | Antique Brass Bezel | | | | | | | 80 | 1 |

Supplied with a toolless loop-in/loop-out quick connector. * Part L Compliant of UK Building Regulations. Part B Compliant BS476 Parts 21 and 22. Suitable for 30 minute 600mm/15mm single layer standard wallboard, 60 minute 600mm/12.5mm twin layer fireboard and 90 minute 450mm/15mm twin layer fireboard ceilings.



This luminaire contains built-in LED lamps.

LED

The lamps cannot be changed in the luminaire.

CROMPTON LAMPS 874/2012

10W Dimmable Spotlight

2W Dimmable Rim

Bluetooth App Control

Individual or Group Control

5 YEAR WARRANTY

Lighting brilliance since 1878



Phoebe LED™ is a trading name of Crompton Lamps Limited
 Crompton Lamps Limited registered in England and Wales No. 05590551
 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE
Tel: +44 (0)1274 657 088 **Fax:** +44 (0)1274 657 087 **Email:** sales@cromptonlamps.com **Web:** www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice.
 E. & O. E. © Crompton Lamps Limited 2018