

MANTOZ INTEGRATEDZ

ID/E routed	forvert	vuo artia ar	autoloar	
IP65 rated	IOI WEL	weamer	CUICICO	use

- Suitable for conduit, surface, or suspension mounting
- Loop-in/Loop-out terminal blocks for continuous fitting-to-fitting live feed
- 3 hour emergency function*

11

Microwave sensor with variable detection range, hold time and lux sensors**

- Ideal for use in industrial, garage, workshop and food preparation applications
- Constructed from IK07 impact rated, moisture and acid resistant ABS body with Polycarbonate diffuser

RA ≥80 4000K Cool White P Rating	50,000 Hours Average Rated Life Beam Angle	3 Hour Emergency	Microwave Sensor	9
Code Product Name	Watts Colour	Total Beam Lumens Angle	Width Height Length MOQ	
4ft Standard				
11021 LED Non-Corrosive 4ft	20 4000K Cool White	2000lm 120°	85mm 75mm 1270mm 1	
11038 LED Non-Corrosive 4ft with Microwave Sensor	20 4000K Cool White	2000lm 120°	85mm 75mm 1270mm 1	
11045 LED Non-Corrosive 4ft with 3-Hour Emergency	20 4000K Cool White	2000lm 120°	85mm 75mm 1270mm 1	
4ft High Output				

4ft High Output								
11052	LED Non-Corrosive 4ft	40	4000K Cool White	4000lm	120°	118mm	75mm 1270mm	1
11069	LED Non-Corrosive 4ft with Microwave Sensor	40	4000K Cool White	4000lm	120°	118mm	75mm 1270mm	1
11076	LED Non-Corrosive 4ft Twin with 3-Hour Emergency	40	4000K Cool White	4000lm	120°	118mm	75mm 1270mm	1
5ft Standard								
11083	LED Non-Corrosive 5ft Single	30	4000K Cool White	3000lm	120°	85mm	75mm 1570mm	1
11090	LED Non-Corrosive 5ft Single with Microwave Sensor	30	4000K Cool White	3000lm	120°	85mm	75mm 1570mm	1
11106	LED Non-Corrosive 5ft Single with 3-Hour Emergency	30	4000K Cool White	3000lm	120°	85mm	75mm 1570mm	1
5ft High Output								
11113	LED Non-Corrosive 5ft Twin	60	4000K Cool White	6000lm	120°	118mm	75mm 1570mm	1
11120	LED Non-Corrosive 5ft Twin with Microwave Sensor	60	4000K Cool White	6000lm	120°	118mm	75mm 1570mm	1

1113	LED NON-Corrosive Str I win	60	4000K COOI White	6000IM	120°	118mm	75mm 1570mm	I	_
1120	LED Non-Corrosive 5ft Twin with Microwave Sensor	60	4000K Cool White	6000lm	120°	118mm	75mm 1570mm	1	_
1137	LED Non-Corrosive 5ft Twin with 3-Hour Emergency	60	4000K Cool White	6000lm	120°	118mm	75mm 1570mm	1	

Lighting brilliance since 1878

Phoebe LED™ is a trading name of Crompton Lamps Limited Crompton Lamps Limited registered in England and Wales No. 05590551 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com

* EM Discharge ≥ 3 Hours, 16 hour charge time required.

Suitable for Outdoor Use

** 5m - 10m Detection range, 5s - 10min Hold time, 2-2000lum light sensitivity, light sensor Dims to 10% light output when sensor not triggered.

All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. © Crompton Lamps Limited 2019