

# Photius Integrated LED Batten CCT



Flicker free linear batten with a sleek and slim design. Fitted with CCT technology to change the colour temperature of the LED between warm white, cool white or daylight. Available in 4ft/5ft lengths as either standard, with built-in microwave sensor or with integrated 3-hour emergency module.

- 35,000 hours long life maintenance free operation
- Constructed from an aluminium body with a polycarbonate diffuser
- Tri-colour selection switch 3000K/4000K and 6000K
- High efficiency 120lm/W
- Standard 4ft or 5ft lengths
- Colour rendering index Ra≥80
- Not suitable for dimming

| Product Code                              | Product Description       | Watts (W) | Volts (V) | Colour Temp (K) | Total Lumens (lm) | Beam Angle | Dimensions (mm) |    |      | Order Qty |
|---|---------------------------|-----------|-----------|-----------------|-------------------|------------|-----------------|----|------|-----------|
|   |                           |           |           |                 |                   |            | W               | H  | L    |           |
| <b>Standard - Single Carton</b>           |                           |           |           |                 |                   |            |                 |    |      |           |
| 12219                                     | 4ft Standard              | 40        | 240       | 3000/4000/6000  | 4800              | 120°       | 80              | 36 | 1190 | 1         |
| 12240                                     | 5ft Standard              | 60        | 240       | 3000/4000/6000  | 7200              | 120°       | 80              | 36 | 1490 | 1         |
| <b>Microwave Sensor* - Single Carton</b>  |                           |           |           |                 |                   |            |                 |    |      |           |
| 12226                                     | 4ft with Microwave Sensor | 40        | 240       | 3000/4000/6000  | 4800              | 120°       | 80              | 36 | 1190 | 1         |
| 12257                                     | 5ft with Microwave Sensor | 60        | 240       | 3000/4000/6000  | 7200              | 120°       | 80              | 36 | 1490 | 1         |
| <b>3-Hour Emergency** - Single Carton</b> |                           |           |           |                 |                   |            |                 |    |      |           |
| 12233                                     | 4ft with Emergency Module | 40        | 240       | 3000/4000/6000  | 4800              | 120°       | 80              | 36 | 1190 | 1         |
| 12264                                     | 5ft with Emergency Module | 60        | 240       | 3000/4000/6000  | 7200              | 120°       | 80              | 36 | 1490 | 1         |

\* 6m Detection range, 5s-10min Hold time 5-∞lum light sensor Instant off or 20% light output after hold time when sensor not triggered, 30s-∞ dimming level hold  
 \*\* Emergency Discharge ≥ 3 Hours at 960lm, 24 hour charge time required, Built in Emergency test function. Fitted with a 4 Way Terminal block for Permanent Live

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

CROMPTON LAMPS

LED

874/2012

IP Rating

Microwave Sensor

3 Hour Emergency

5 YEAR WARRANTY

*Lighting brilliance since 1878*

Phoebe LED™ is a trading name of Crompton Lamps Limited  
 Crompton Lamps Limited registered in England and Wales No. 05590551  
 Registered office and correspondence address: Unit 2, Marttree Business Park, Bowling Back Lane, Bradford BD4 8QE  
**Tel:** +44 (0)1274 657 088 **Fax:** +44 (0)1274 657 087 **Email:** sales@cromptonlamps.com **Web:** www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice.  
 E. & O. E. © Crompton Lamps Limited 2019