

LED Thermal Plastic GU10 SMD




Energy efficient LED GU10 lamp with thermal plastic heat dissipating body. Suitable for fire rated downlights.

- 15,000 hour life
- 2700K warm white or 3000K warm white plus 4000K cool white and 6500K daylight colour options
- Colour rendering index Ra≥80
- GU10 cap
- Suitable for fire rated downlights
- Dimmable or non-dimmable options
- Dimmable option utilizes DuoDim™ Technology compatible with both leading and trailing edge dimmers*
- Recommended for indoor use only

Product Code	Watts (W)	Volts (V)	Cap	Colour Appearance	Colour Temp (K)	Useful Lumens (lm)	Total Lumens (lm)	Halogen Equiv. (W)	Beam Angle	Dimensions (mm)		Energy Rating	Order Qty
										Dia	H		
Single Carton - Non-Dimmable													
16941	5	240	GU10	Warm White	2700	385	480	75	38°	50	56		10
16958	5	240	GU10	Warm White	3000	400	500	75	38°	50	56		10
16965	5	240	GU10	Cool White	4000	440	550	75	38°	50	56		10
16972	5	240	GU10	Daylight	6500	440	550	75	38°	50	56		10
Single Carton - Dimmable*													
16682	5	240	GU10	Warm White	2700	385	480	75	38°	50	56		10
16699	5	240	GU10	Warm White	3000	400	500	75	38°	50	56		10
16705	5	240	GU10	Cool White	4000	440	550	75	38°	50	56		10
16712	5	240	GU10	Daylight	6500	440	550	75	38°	50	56		10

* The lamp is compatible with most dimmer switches, please refer to website for up-to-date list of compatible dimmer switches.



GU10 Cap



Lighting brilliance since 1878

LED Thermal Plastic GU10 SMD



The below table is designed to help you choose a suitable dimmer switch for your Crompton Lamp dimmable product. Crompton Lamps have extensively tested the below dimmer switches to evaluate their dimming function and to make sure the dimmer switch meets our dimming compatibility standards.

All compatible dimmer switches may require low end trimming.

For guidelines on dimmer switches not listed below, or for more information please contact Crompton Lamps.

Brand	Model	Wattage	Pass	Fail	Notes
Click	MD9042	60-400W	X		Smooth
MK	M2149R	4-70W (LED)	X		Slight Buzz from lamps
Hamilton	LED1TB	5-100W		X	Fail
Zano	ZME250	5-250W		X	Fail - Flickering
Varilight	V-Pro	0-120W		X	Fail - Flickering
Varilight	V-Pro	0-300W	X		Smooth
Varilight	V-Pro	0-400W	X		Smooth
Zano	ZMC150	0-150W		X	Fail - Flickering
HZC Electric	UK-P5	5-250W	X		Smooth
Crompton	14671	0-220W		X	Fail - Slight Flickering

Lighting brilliance since 1878