

PHOEBE LED MANTO INTEGRATED 2 LED LUMINAIRE

Featuring Two Tool-Less, Loop-Through Terminal Blocks with Continuous Live Feed



Standard, Microwave Sensor and Emergency Models Available

- Loop-through continuous live feed
- IP65 rated for outdoor use
- High output options
- Non-corrosive



Non-Corrosive IP65 Integrated LED Fitting

The Manto 2 is an IP65 integrated LED fitting. It is available in standard and high output in 4ft and 5ft lengths with the choice of microwave sensor and 3 hour emergency options.

It has been designed with easy installation in mind and features two tool-less, loop-through terminal blocks with continuous live feed.

Constructed with an IK07 impact rated, moisture and acid resistant ABS body with Polycarbonate diffuser, the Manto 2 has been developed to be robust, durable and is suitable for conduit, surface, or suspension mounting.

- 50.000 hour life
- O 100,000 switching cycles
- O Loop-through continuous live feed
- O 120° beam angle
- O 4000K colour temperature
- O Colour rendering index ≥80
- O IP65 rated
- O Internal terminal block for safety
- O IK07 impact rating
- O 5 year warranty

Durability, Reliability & Easy Installation

Developed and designed to be the ideal solution for industrial applications such as car parks, garages and workshops where quality, dependability and hassle free installation is required.



Crompton Lamps Limited Unit 2 Marrtree Business Park **Bowling Back Lane** Bradford BD4 8QE

Tel: 01274 657 088 Fax: 01274 657 087

Email: sales@cromptonlamps.com www.cromptonlamps.com

Trade Descriptions: All descriptions represent only particulars of the goods to which they apply and do not form part of any contract. Due to policy of continuous development and improvement, Crompton Lamps Limited reserves the right to change the specification and performance data of the products listed without prior notice or public announcement.





s Thro



Fully IP65 Rated



One of the many key features of the Manto 2 is its IP65 rating. This rating ensures the Manto 2 can be utilised in a variety of wet conditions.

Benefits of an IP65 rating

- Protected against water in all directions
- Suitable for wet weather outdoor use
- Complete protection against contact dust

IK07 Impact rating

Excellent Cost Savings

With low wattages across the range, 50,000 hour life and 100,000 switching cycles, the Manto 2 will save you money.

20W Annual running cost

30W Annual running cost

40W Annual running cost

60W Annual running cost

£7.34

£14.69

£22.03

All above figures are based on annual usage 7hrs/day @ £0.1437kWhr

Crompton Lamps Limited Unit 2 Marrtree Business Park **Bowling Back Lane** Bradford BD4 8QE

Tel: 01274 657 088 Fax: 01274 657 087

Email: sales@cromptonlamps.com www.cromptonlamps.com




Loop-Through Continuous Live Feed

What makes the Manto 2 stand out from the competition is the key ability to have a continuous live feed from fitting-to-fitting thanks to its two loop-through terminal blocks. This unique feature saves any electrician/contractor an enormous amount of time on projects that require multiple fittings to be installed.

Benefits of Loop-In/Loop-Out

- O Tool-less wiring connector
- O Simplifies the installation process
- O Reduces time required for installation
- O Permanent live for use with emergency models





Loop through continuous live feed



The loop-in/loop-out terminals make it possible to wire from fitting-to-fitting

Crompton Lamps Limited Unit 2 Marrtree Business Park Bowling Back Lane Bradford BD4 8QE Tel: 01274 657 088 Fax: 01274 657 087 Email: sales@cromptonlamps.com www.cromptonlamps.com






High Output - Equivalent Replacement for Twin Fluorescent T8 Fittings



Standard - Equivalent Replacement for Single Fluorescent T8 Fittings



Crompton Lamps Limited

Unit 2 Marrtree Business Park Bowling Back Lane Bradford BD4 8QE

Tel: 01274 657 088 Fax: 01274 657 087

Email: sales@cromptonlamps.com www.cromptonlamps.com



Microwave Sensor

	•
	•

O 5m - 10m Detection Range O 5secs - 10min Hold Time O 2-2000lux Light Sensitivity

O Light output dims to 10% when sensor not triggered

Emergency

	-		
			•
		Self-test button	

O Discharge \geq 3 Hours O 16 hour Charge Time

Crompton Lamps Limited


Unit 2 Marrtree Business Park Bowling Back Lane Bradford BD4 8QE Tel: 01274 657 088 Fax: 01274 657 087 Email: sales@cromptonlamps.com www.cromptonlamps.com



Technical Information

Non-Corrosive IP65 Integrated LED Fitting

- O 50,000 hour life
- O 100,000 switching cycles
- O Loop-through continuous live feed
- O 120° beam angle
- O 4000K colour temperature
- O Colour rendering index ≥80
- O IP65 rated
- O Internal terminal block for safety
- O IK07 impact rating
- O 5 year warranty





Product Code	Watts (W)	Volts (V)	Product Description	Colour Temp	Total Lumens	Beam Angle	Dimensions (mm)			Order Qty
				(K)	(lm)		W	Н	L	
4ft Stande	ard - Sin	gle Car	łon							
11021	20	240	4ft	4000K	2000	120°	85	75	1270	1
11038	20	240	4ft with Microwave Sensor	4000K	2000	120°	118	75	1270	1
11045	20	240	4ft with 3-Hour Emergency	4000K	2000	120°	85	75	1270	1
4ft High C	Output -	Single C	Carton							
11052	40	240	4ft	4000K	4000	120°	118	75	1270	1
11069	40	240	4ft with Microwave Sensor	4000K	4000	120°	118	75	1270	1
11076	40	240	4ft with 3-Hour Emergency	4000K	4000	120°	118	75	1270	1
5ft Standard - Single Carton										
11083	30	240	5ft	4000K	3000	120°	85	75	1570	1
11090	30	240	5ft with Microwave Sensor	4000K	3000	120°	118	75	1570	1
11106	30	240	5ft with 3-Hour Emergency	4000K	3000	120°	85	75	1570	1
5ft High C	5ft High Output - Single Carton									
11113	60	240	5ft	4000K	6000	120°	118	75	1570	1
11120	60	240	5ft with Microwave Sensor	4000K	6000	120°	118	75	1570	1
11137	60	240	5ft with 3-Hour Emergency	4000K	6000	120°	118	75	1570	1



Crompton Lamps Limited

Unit 2 Marrtree Business Park Bowling Back Lane Bradford BD4 8QE Tel: 01274 657 088 Fax: 01274 657 087 Email: sales@cromptonlamps.com www.cromptonlamps.com







Other fantastic Phoebe LED products that may interest you...



Photius T8 Batten

Robust steel T8 batten pre-wired to mains (240V) for use with Crompton Lamps LED T8 tubes only. Constructed from a robust steel body with white gloss powder coated finish, polycarbonate end caps and fused terminal block for safety.

Visit our website and view our full range of lamps and fittings

Benefits of signing up:

- O Online ordering
- O Special offers
- O Check stock and prices
- O View order history
- O Detailed product information
- O View our comprehensive range



Crompton Lamps Limited Unit 2 Marrtree Business Park Bowling Back Lane Bradford BD4 8QE

Tel: 01274 657 088 Fax: 01274 657 087 Email: sales@cromptonlamps.com www.cromptonlamps.com





Design and production by Marketing, Crompton Lamps Limited E. & O. E. © Crompton Lamps Limited 2019. All rights reserved.

