



Atlanta Universal LED Downlight

30,000 hour life, 50,000 Switching Cycles							
Features universal multi-fit adjustable bracket							
> 6.5W fits recesses of Ø 63.5-102mm, 18.5W fits recesses of Ø 63.5-203mm							
Surface mount or recessed installation							
Constructed from corrosion resistant thermal plastic with a corrosion							
resistant PS diffuser							
> 3000K warm white or 4000K cool white colour options							
	All Purpose Downlight Red	rface Mounted or cessed Installation		ersal fit ble bracket		lim-line ern Design	
		0,000 ,itching Cycles , by cles	Maintenance	2.5" - 4" 2.5" - 8" Recessed Installations	Surface Mountab	Non-Dimmable & Dimmable Versions	
Code	Product Name	Watts Colour To	otal Lumens B	eam Angle Dia	meter Height	Cutout Price	
	mable - Single Carton						
10536	Atlanta Universal LED Downlight Atlanta Universal LED Downlight	18.5 3000K Warm White   18.5 4000K Cool White	1550lm 1600lm		0mm 15mm 0mm 15mm	63.5-203mm 63.5-203mm	
	le - Single Carton			120 23		00.0-20011111	
12172	Atlanta Universal LED Downlight	6.5 3000K Warm White	440lm	120° 12	0mm 15mm	63.5-102mm	
12189	Atlanta Universal LED Downlight	6.5 4000K Cool White	460lm		0mm 15mm	63.5-102mm	
12196	Atlanta Universal LED Downlight	18.5 3000K Warm White	1550lm	120° 23	0mm 15mm	63.5-203mm	
10000							
12202	Atlanta Universal LED Downlight	18.5 4000K Cool White	1600lm	120° 23	0mm 15mm	63.5-203mm	