



Photius LED Tri Colour Select
LED integrated luminaire for use in residential, commercial, office and other interior lighting applications

Standard/Emergency

Sensor





- 35,000 hour life (20,000 for emergency)
- 100,000 switching cycles
- Suitable for surface or suspension mount
- Anodized aluminium with Polycarbonate diffuser
- Internal terminal block for safety
- Tri-colour select easy access hidden switch to select 3000K warm white, 4000K cool white or 6000K daylight colour temperature
- Not suitable for dimming

















Code	Product Name	Watts	Volts	Colour	Total Lumens	Width	Length	Height	MOQ
Standard - Single Carton									
12219	Integrated CCT 4ft Batten	40W	240V	Tri-Colour Select	4800	80mm	1200mm	36mm	1
12226	Integrated CCT 5ft Batten	60W	240V	Tri-Colour Select	7200	80mm	1500mm	36mm	1
Microwave Sensor - Single Carton									
12233	Integrated CCT 4ft Batten with Microwave Sensor	40W	240V	Tri-Colour Select	4800	80mm	1200mm	36mm	1
12240	Integrated CCT 5ft Batten with Microwave Sensor	60W	240V	Tri-Colour Select	7200	80mm	1500mm	36mm	1
3-Hour Emergency - Single Carton									
12257	Integrated CCT 4ft Batten with 3-Hour Emergency	40W	240V	Tri-Colour Select	4800	80mm	1200mm	36mm	1
12264	Integrated CCT 5ft Batten with 3-Hour Emergency	60W	240V	Tri-Colour Select	7200	80mm	1500mm	36mm	1

lergency Discharge ≥ 3 Hours, 24 hour charge time required. Built in Emergency test function. Fitted with a 4 Way Terminal block for Permanent Live %-100% Detection rage (Max 6m) 5s-10min Hold time 5-∞lum light sensor Instant off or 20% light output after hold time when sensor not triggered. 30s-∞ dimming level hold.

Phoebe LED^{Im} is a trading name of Crompton Lamps Limited registered in England and Wales No. 05590551 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@phoebeled.com Web: www.phoebeled.com