




Celine LED Commercial Downlight




Energy efficient integrated LED downlight with loop-in loop-out wiring connections.

- Long life 30,000 hours maintenance free operation
- 15,000 switching cycles
- IP44 rated suitable for use in bathrooms (zones 1 & 2)
- Constructed from corrosion resistant thermal plastic and includes aluminium heatsink
- Easy Installation, includes 1m cable pre-wired to input
- 4000K cool white colour temperature
- Colour rendering index Ra≥80
- Ideal replacement for PLC CFL downlights
- Instant full light output
- Back lit design to ensure light is uniform within the beam
- Not suitable for dimmina

Product Code	Watts	Volts (V)	Colour Appearance	Colour Temp (K)	Useful Lumens (Im)	Total Lumens (lm)	Beam Angle	Dimensions (mm)			Order
	(W)							Dia	Н	Cutout Ø	Qty
Single Carton											
6317	15	240	Cool White	4000	990	1200	100°	180	60	160	1
6324	20	240	Cool White	4000	1240	1600	100°	230	60	210	1
6331	30	240	Cool White	4000	2100	2400	100°	230	60	210	1















Phoebe LED™ is a trading name of Crompton Lamps Limited
Crompton Lamps Limited registered in England and Wales No. 05590551
Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE