




Atlas Mini LED Floodlight

IP65 Rated LED floodlight

- ▶ Long life 30,000 hours
- ▶ 4000K cool white colour
- ▶ IP65 rated including PIR and stem
- ▶ Not suitable for dimming



PIR Sensor models:

- Controls for sensitivity, time and lux levels
- Maximum detection range selectable up to 8m
- 120° monitoring angle
- Light hold after detection selectable from 10 seconds to 7 minutes
- Override option for PIR models*

Fully IP65 Rated including PIR
Diecast Aluminium Powder Coating
4000K Cool White
80cm VDE Cable Attached



4000K
Cool White

IP65
IP Rating

35,000
Hours Average Rated Life

15,000
Switching Cycles

110°
Beam Angle

Maintenance Free

Non-Dimmable

Code	Product Name	Watts	Useful Lumens	Total Lumens	Beam Angle	Height	Width	Depth (inc PIR)	Price
Atlas Mini Slimline floodlight - NON PIR									
12554	Atlas-Mini Slimline Floodlight	10W	900lm	1000lm	110°	102mm	127mm	26mm	
12561	Atlas-Mini Slimline Floodlight	20W	1800lm	2000lm	110°	121mm	159mm	28mm	
12578	Atlas-Mini Slimline Floodlight	30W	2700lm	3000lm	110°	145mm	197mm	29mm	
12585	Atlas-Mini Slimline Floodlight	50W	4500lm	5000lm	110°	178mm	243mm	32mm	
Atlas Mini Slimline floodlight - WITH PIR									
12592	Atlas-Mini Slimline Floodlight with PIR Sensor	10W	900lm	1000lm	110°	149mm	127mm	55mm	
12608	Atlas-Mini Slimline Floodlight with PIR Sensor	20W	1800lm	2000lm	110°	169mm	159mm	55mm	
12615	Atlas-Mini Slimline Floodlight with PIR Sensor	30W	2700lm	3000lm	110°	191mm	197mm	55mm	
12622	Atlas-Mini Slimline Floodlight with PIR Sensor	50W	4500lm	5000lm	110°	224mm	243mm	55mm	

*Includes override function - turn on/off/on to override PIR

Lighting brilliance since 1878