






- IP65 rated for wet weather outdoor use
- Suitable for conduit, surface, or suspension mounting
- 3 hour emergency function*
- Microwave sensor with variable detection range, hold time and lux sensors**
- Ideal for use in industrial, garage, workshop and food preparation applications
- Constructed from IK07 impact rated, moisture and acid resistant ABS body with Polycarbonate diffuser



Suitable for
Outdoor Use

* EM Discharge ≥ 3 Hours, 16 hour charge time required.

** 25%-100% Detection range (Max 10m)
5s-30min Hold time 2-2000lum light sensor
Dims to 15% light output when sensor not triggered.



Code	Product Name	Watts	Colour	Total Lumens	Beam Angle	Width	Height	Length	Price
11021	LED Non-Corrosive 4ft Single	20	4000K Cool White	2000lm	120°	85mm	75mm	1270mm	
11038	LED Non-Corrosive 4ft Single with Microwave Sensor	20	4000K Cool White	2000lm	120°	85mm	75mm	1270mm	
11045	LED Non-Corrosive 4ft Single with 3-Hour Emergency	20	4000K Cool White	2000lm	120°	85mm	75mm	1270mm	
11052	LED Non-Corrosive 4ft Twin	40	4000K Cool White	4000lm	120°	118mm	75mm	1270mm	
11069	LED Non-Corrosive 4ft Twin with Microwave Sensor	40	4000K Cool White	4000lm	120°	118mm	75mm	1270mm	
11076	LED Non-Corrosive 4ft Twin with 3-Hour Emergency	40	4000K Cool White	4000lm	120°	118mm	75mm	1270mm	
11083	LED Non-Corrosive 5ft Single	30	4000K Cool White	3000lm	120°	85mm	75mm	1570mm	
11090	LED Non-Corrosive 5ft Single with Microwave Sensor	30	4000K Cool White	3000lm	120°	85mm	75mm	1570mm	
11106	LED Non-Corrosive 5ft Single with 3-Hour Emergency	30	4000K Cool White	3000lm	120°	85mm	75mm	1570mm	
11113	LED Non-Corrosive 5ft Twin	60	4000K Cool White	6000lm	120°	118mm	75mm	1570mm	
11120	LED Non-Corrosive 5ft Twin with Microwave Sensor	60	4000K Cool White	6000lm	120°	118mm	75mm	1570mm	
11137	LED Non-Corrosive 5ft Twin with 3-Hour Emergency	60	4000K Cool White	6000lm	120°	118mm	75mm	1570mm	