



MELANA

LED ROUND BULKHEAD

IP66
IK10

15W Energy Efficient Integrated Round Bulkhead

IP66 Ingress Rating, IK10 Impact Rating with various options including eyelid cover, microwave sensor and 3 hour emergency

- Suitable for wall or ceiling mounting, indoors or outdoors
- Built-in safety isolating control gear with short circuit protection
- Microwave sensor* and Emergency** options
- Long life 35,000 hours maintenance free operation
- IP66 rated suitable for outdoor use
- 3000K warm white and 4000K cool white colour options
- Available in Black or white finish with opal diffuser and optional eyelid cover
- Constructed from tough polycarbonate with IK10 impact rating



Code	Product Name	Watts	Colour Temp	Useful Lumens	Total Lumens	Beam Angle	Diameter	Depth	Price
Standard - Single Carton									
10628	Melana IP66 LED round bulkhead in white	15W	3000K	1100lm	1300lm	110°	308mm	89mm	
6492	Melana IP66 LED round bulkhead in white	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
10635	Melana IP66 LED round bulkhead in black	15W	3000K	1100lm	1300lm	110°	308mm	89mm	
6508	Melana IP66 LED round bulkhead in black	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
Microwave Sensor* - Single Carton									
10239	Melana IP66 Sensor LED round bulkhead in white	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
10291	Melana IP66 Sensor LED round bulkhead in black	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
3 Hour Emergency** - Single Carton									
10253	Melana IP66 Emergency LED round bulkhead in white	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
10307	Melana IP66 Emergency LED round bulkhead in black	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
Microwave Sensor* and 3 Hour Emergency** - Single Carton									
10277	Melana IP66 Sensor and Emergency LED round bulkhead in white	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
10260	Melana IP66 Sensor and Emergency LED round bulkhead in black	15W	4000K	1100lm	1300lm	110°	308mm	89mm	
Accessories - Single Carton									
10277	Melana round bulkhead eyelid in white						308mm		
10260	Melana round bulkhead eyelid in black						308mm		

* Microwave sensor range 5m - 7m, 140° angle, hold time 30 seconds, dims to 10% when no detection.

** Charging time 24hrs - Running time 3hrs at 20% light output.

Lighting brilliance since 1878

