

**PHOEBE  
LED**

**MANTO2**  
INTEGRATED2



- ▶ IP65 rated for wet weather outdoor use
- ▶ Suitable for conduit, surface, or suspension mounting
- ▶ Loop-in/Loop-out terminal blocks for continuous fitting-to-fitting live feed
- ▶ 3 hour emergency function\*
- ▶ Microwave sensor with variable detection range, hold time and lux sensors\*\*
- ▶ Ideal for use in industrial, garage, workshop and food preparation applications
- ▶ Constructed from IK07 impact rated, moisture and acid resistant ABS body with Polycarbonate diffuser



Suitable for  
Outdoor Use

\* EM Discharge ≥ 3 Hours, 16 hour charge time required.

\*\* 5m - 10m Detection range, 5s - 10min Hold time, 2-2000lux light sensitivity, light sensor Dims to 10% light output when sensor not triggered.



RA ≥80  
4000K  
Cool White

IP65  
IP Rating

50,000  
Hours Average  
Rated Life

120°  
Beam Angle

3  
Hours  
3 Hour  
Emergency

Microwave  
Sensor

Non-Dimmable

Code	Product Name	Watts	Colour	Total Lumens	Beam Angle	Width	Height	Length	DFWV
<b>4ft Standard</b>									
11021	LED Non-Corrosive 4ft	20	4000K Cool White	2000lm	120°	85mm	75mm	1270mm	
11038	LED Non-Corrosive 4ft with Microwave Sensor	20	4000K Cool White	2000lm	120°	85mm	75mm	1270mm	
11045	LED Non-Corrosive 4ft with 3-Hour Emergency	20	4000K Cool White	2000lm	120°	85mm	75mm	1270mm	
<b>4ft High Output</b>									
11052	LED Non-Corrosive 4ft	40	4000K Cool White	4000lm	120°	118mm	75mm	1270mm	
11069	LED Non-Corrosive 4ft with Microwave Sensor	40	4000K Cool White	4000lm	120°	118mm	75mm	1270mm	
11076	LED Non-Corrosive 4ft Twin with 3-Hour Emergency	40	4000K Cool White	4000lm	120°	118mm	75mm	1270mm	
<b>5ft Standard</b>									
11083	LED Non-Corrosive 5ft Single	30	4000K Cool White	3000lm	120°	85mm	75mm	1570mm	
11090	LED Non-Corrosive 5ft Single with Microwave Sensor	30	4000K Cool White	3000lm	120°	85mm	75mm	1570mm	
11106	LED Non-Corrosive 5ft Single with 3-Hour Emergency	30	4000K Cool White	3000lm	120°	85mm	75mm	1570mm	
<b>5ft High Output</b>									
11113	LED Non-Corrosive 5ft Twin	60	4000K Cool White	6000lm	120°	118mm	75mm	1570mm	
11120	LED Non-Corrosive 5ft Twin with Microwave Sensor	60	4000K Cool White	6000lm	120°	118mm	75mm	1570mm	
11137	LED Non-Corrosive 5ft Twin with 3-Hour Emergency	60	4000K Cool White	6000lm	120°	118mm	75mm	1570mm	

Lighting brilliance since 1878