





# Lykos IP65 Integrated CCT Battens



IP65 integrated fittings for use in industrial, garage, workshop and food preparation applications

- Suitable for conduit, surface, or suspension mounting
- Constructed from tough IK08 impact rated, moisture and acid resistant Polycarbonate body and diffuser
- IP65 rated for wet weather outdoor use
- 3000K/4000K/5700K Tri-Colour Select
- Pre-wired with toolless spade terminals with pass-through loop-in loop-out including permanent live for use with emergency models
- 50,000 hour long life
- 100,000 switching cycles
- 120° beam angle
- Colour rendering index ≥80
- Ambient operating temp. -20°C to 40°C (0°C to 40°C for Emergency versions)
- Available with 3 hour emergency function and Microwave Sensor Models

Product Code	Product Description	Watts (W)	Volts (V)	Colour Temp (K)	Total Lumens (lm)	Beam Angle	Dimensions (mm)			Order Qty
							W	H	L	
<b>Standard - Single Carton</b>										
14251	4ft Batten	20	240	3000K/4000K/5700K	2000	120°	80	72	1200	1
14275	5ft Batten	30	240	3000K/4000K/5700K	3000	120°	80	72	1500	1
<b>Microwave Sensor - Single Carton</b>										
14749	4ft Batten with Microwave Sensor	20	240	3000K/4000K/5700K	2000	120°	80	72	1200	1
14701	5ft Batten with Microwave Sensor	30	240	3000K/4000K/5700K	3000	120°	80	72	1500	1
<b>Emergency - Single Carton</b>										
14268	4ft Batten with 3-Hour Emergency	20	240	3000K/4000K/5700K	2000	120°	80	72	1200	1
14282	5ft Batten with 3-Hour Emergency	30	240	3000K/4000K/5700K	3000	120°	80	72	1500	1
<b>High Output - Single Carton</b>										
14299	High Output (HO) 4ft Batten	40	240	3000K/4000K/5700K	4000	120°	105	87	1200	1
14312	High Output (HO) 5ft Batten	60	240	3000K/4000K/5700K	6000	120°	105	87	1500	1
14336	High Output (HO) 6ft Batten	80	240	3000K/4000K/5700K	8000	120°	105	87	1800	1
<b>Emergency High Output - Single Carton</b>										
14305	HO 4ft Batten with 3-Hour Emergency	40	240	3000K/4000K/5700K	4000	120°	105	87	1200	1
14329	HO 5ft Batten with 3-Hour Emergency	60	240	3000K/4000K/5700K	6000	120°	105	87	1500	1
14343	HO 6ft Batten with 3-Hour Emergency	80	240	3000K/4000K/5700K	8000	120°	105	87	1800	1



\* **EM Discharge** ≥ 3 Hours, 24 hour charge time required.

Microwave sensor with adjustable settings.


**Detection Sensitivity:** Upto 1.5/3/4.5/6 Meters

**Hold Time:** 5/30/90 Seconds 5/20/30 Minutes

**Daylight Threshold:** 2/10/30/50 lux or off



Lighting brilliance since 1878



Phoebe LED™ is a trading name of Crompton Lamps Limited  
Crompton Lamps Limited registered in England and Wales No. 05590551

Registered office and correspondence address: Unit 2, Martree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice.  
E. & O. E. © Crompton Lamps Limited 2023