

# LED Mini Link-Light




Be your own lighting designer with these high quality customizable under-cabinet LED lights. Featuring an ultra-slim design in a variety of lengths. Connectors, leads, switches and drivers are also available.

- 40,000 hour life
- 20,000 switching cycles
- 3000K warm white or 4000K cool white colour options
- Colour rendering index Ra≥82
- Phoebe LED driver required
- Dimmable - using optional dimmer switch (product code:5020)
- IP20 rated for indoor use only

Product Code	Product Description	Watts (W)	Volts (V)	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Beam Angle	Dimensions (mm)			Order Qty
								W	H	L	
<b>LED Mini Link-Light - Single Carton</b>											
4894	LED Mini Link-Light 15cm	2.5	24	Warm White	3000	195	100	18	8	150	1
4900	LED Mini Link-Light 30cm	5	24	Warm White	3000	325	100	18	8	300	1
4917	LED Mini Link-Light 60cm	9	24	Warm White	3000	590	100	18	8	600	1
4924	LED Mini Link-Light 100cm	15	24	Warm White	3000	975	100	18	8	1000	1
4931	LED Mini Link-Light 15cm	2.5	24	Cool White	4000	195	100	18	8	150	1
4948	LED Mini Link-Light 30cm	5	24	Cool White	4000	325	100	18	8	300	1
4955	LED Mini Link-Light 60cm	9	24	Cool White	4000	590	100	18	8	600	1
4962	LED Mini Link-Light 100cm	15	24	Cool White	4000	975	100	18	8	1000	1
<b>Power Supply - Single Carton</b>											
4979	20W Driver & On/Off Switch	20	240					40	22	125	1
4986	36W Driver & On/Off Switch	36	240					51.5	31.5	103	1
4993	60W Driver & On/Off Switch	60	240					52.5	30	115	1
5006	120W Driver & On/Off Switch	120	240					65.5	35	162	1
<b>Switches - Single Packet</b>											
5013	Additional Touch Sensitive On/Off Switch							18	8	67	1
5020	Touch Sensitive Dimmer Switch							18	8	67	1
5037	Motion Sensor On/Off Switch							18	8	67	1
<b>Link-Leads - Single Packet</b>											
5068	4-Way Adapter Lead									500	1
5044	Additional Power Lead									500	1
5051	Link-Lead (Male to Male) - Flexibly Connects Link-Light to Link-Light									500	1
5648	Link Lead (Female to Male) - Flexibly Connects Switch to Link-Light									500	1
<b>Connectors - Single Packet</b>											
5075	2-Way Connector Left							20	12	20	1
5082	2-Way Connector Right							20	12	20	1
5099	3-Way Connector T-Shaped							20	12	20	1
5105	4-Way Connector							20	12	20	1
5112	Internal Corner Connector							20	12	12	1
<b>Mounting Brackets - Single Packet</b>											
5129	Replacement Mounting Brackets (Pack of 4)										1
5136	45° Angled Mounting Brackets (Pack of 4)										1
<b>Point-of-Sale Marketing</b>											
4891	LED Mini Link-Light Foam Slat-Wall Header Card							800	300		1
4892	LED Mini Link-Light Interactive Display Board							400	300		1
4893	LED Mini Link-Light Pack of 50 Flyers							99	210		1

Mini Link-Light includes: 1x Mini Link-Light Length, 1x Clear Connector, 1x Clear End Cap and 2x Mounting Brackets.  
 Mini Link-Light Power Supply includes: 1x Power Supply, 1x Touch Sensitive On/Off Switch, Power Leads, 3M Adhesive Pads.



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

CROMPTON LAMPS

874/2012

Lighting brilliance since 1878



Phoebe LED™ is a trading name of Crompton Lamps Limited  
 Crompton Lamps Limited registered in England and Wales No. 05590551  
 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@phoebeled.com Web: www.phoebeled.com

All images and specifications are for illustration purposes only and are subject to change without notice.  
 E. & O. E. © Crompton Lamps Limited 2018