


LED T5 Full Glass Tube Direct to Mains





LED T5 full glass tube with external diffused sleeve providing 270° light output. Energy saving with low power consumption. Direct to mains for maximum efficiency no ballast required*. Instant full light.

- 40,000 hour life
- 15,000 switching cycles
- 4000K cool white
- Available in 2ft, 3ft, 4ft or 5ft T5 lengths
- Colour rendering index Ra≥80
- Ambient operating temperature -20°C to 50°C
- No mercury no warping, no bending
- No discolouration of light over life of tube
- Not suitable for dimming
- Not suitable for emergency circuits
- Recommended for indoor use only
- Supplied in a rigid 2mm cardboard tube to minimise transportation damage

Product Code	Watts (W)	Volts (V)	Cap	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Beam Angle	Dimensions (mm)			Energy Rating	Order Qty
								Dia	L1	L2		
Single Carton												
12080	8	240	G5	Cool White	4000	780	270°	16	563	549		1
12097	12	240	G5	Cool White	4000	1100	270°	16	863	849		1
12066	16	240	G5	Cool White	4000	1580	270°	16	1163	1149		1
12073	20	240	G5	Cool White	4000	2400	270°	16	1463	1449		1

* Direct to mains only. Do not run with a ballast, re-wiring by a qualified person may be required, see website for instructions.



Lighting brilliance since 1878