



PHOEBE LED ATLAS-MINI IP65 Rated Slimline Floodlights

Mains operated IP65 Slimline LED Floodlights, ideal for illuminating gardens, patio areas, driveways and pathways or for up-lighting outdoor features.

- Fully IP65 rated including PIR sensor
- Die-cast aluminium, black powder coat finish
- -20°C to 40°C operating temperature
- Angled mounting bracket for easy installation
- Includes 80cm VDE cable

PIR Sensor Models

- Controls for time, sensitivity and lux levels
- 120° monitoring angle
- Maximum detection range selectable up to 8m
- Light hold after detection selectable from 10 seconds to 8 minutes



Available in standard and with PIR sensor which includes a mains switch override option for longer illumination periods.



10W, 20W, 30W and 50W models, providing a powerful range of floodlights for lighting small to large outdoor areas.





Technical Information

IP65 Rated Slimline Floodlights

- Fully IP65 rated including PIR sensor
- Die-cast aluminium, black powder coat finish
- 4000K colour temperature
- -20°C to 40°C operating temperature
- 30,000 hour life
- 15,000 switching cycles
- Angled mounting bracket for easy installation
- Includes 80cm VDE cable
- 5 year warranty

PIR Sensor Models*

- Controls for time, sensitivity and lux levels
- 120° monitoring angle
- Maximum detection range selectable up to 8m
- Light hold after detection selectable from 10 seconds to 8 minutes



| Product Code | Watts (W) | Volts (V) | Colour Appearance | Colour Temp (K) | Useful Lumens (lm) | Total Lumens (lm) | Beam Angle | Dimensions (mm) | | | Order Qty |
|--|-----------|-----------|-------------------|-----------------|--------------------|-------------------|------------|-----------------|-----|----|-----------|
| | | | | | | | | W | H | D | |
| Atlas-Mini Slimline Floodlight - NON PIR | | | | | | | | | | | |
| 12554 | 10 | 240 | Cool White | 4000 | 900 | 1,000 | 110° | 127 | 102 | 26 | 1 |
| 12561 | 20 | 240 | Cool White | 4000 | 1,800 | 2,000 | 110° | 159 | 121 | 28 | 1 |
| 12578 | 30 | 240 | Cool White | 4000 | 2,700 | 3,000 | 110° | 197 | 145 | 29 | 1 |
| 12585 | 50 | 240 | Cool White | 4000 | 4,500 | 5,000 | 110° | 243 | 178 | 32 | 1 |
| Atlas-Mini Slimline Floodlight - WITH PIR | | | | | | | | | | | |
| 12592 | 10 | 240 | Cool White | 4000 | 900 | 1,000 | 110° | 127 | 149 | 55 | 1 |
| 12608 | 20 | 240 | Cool White | 4000 | 1,800 | 2,000 | 110° | 159 | 169 | 55 | 1 |
| 12615 | 30 | 240 | Cool White | 4000 | 2,700 | 3,000 | 110° | 197 | 191 | 55 | 1 |
| 12622 | 50 | 240 | Cool White | 4000 | 4,500 | 5,000 | 110° | 243 | 224 | 55 | 1 |

*Includes override function - turn on/off/on to override PIR

10W Annual running cost = £3.67

20W Annual running cost = £7.34

30W Annual running cost = £11.01

50W Annual running cost = £18.36

Above figures are based on annual usage 7hrs/day @ £0.1437kWhr



Crompton Lamps Limited registered in England and Wales No: 05590551

Crompton Lamps Limited
Unit 2
Marrtree Business Park
Bowling Back Lane
Bradford
BD4 8QE

Tel: 01274 657 088
Fax: 01274 657 087
Email: sales@cromptonlamps.com



Design and production by Marketing,
Crompton Lamps Limited
E. & O. E. © Crompton Lamps Limited 2023.
All rights reserved.

www.cromptonlamps.com

