

Atlas Mini LED Floodlight Complete Unit IP66 Rated with/without PIR Sensor

Long life 35,000 hours

- 4000K cool white colour
- IP66 rated including PIR and stem
 - Not suitable for dimming

PIR Sensor models:

Controls for time, sensitivity and lux levels
Maximum detection range selectable from 5-12m

LAS-MI

- 120° monitoring angle Light hold after detection selectable from 10 seconds to 8 minutes
- Fitted with 4 Core VDE cable for optional control of multiple floodlights*

Fully IP66 Rated Die including PIR P		d Diecast Al Powder	lumir Coat	nium ing	4000K Cool White			80cm VDE Cable Attached		
YEAR	4000K Cool White	*** 00 IP66 IP Rating	35 Hours Rat	,000 Average ted Life	50,000 Switching Cycles		m Angle	Maintena Free	nce	n-Dimmable
Code Produc	Name		Watts	Useful Lumens	Total Lumens	Beam Anale	Height	Width	Depth (inc PIR)	Price
Atlas Mini Slimline floodlight - NON PIR										
7581 Atlas-Mini Slimline Floodlight in Black			10W	760lm	900lm	110°	130mm	140mm	30mm	
10314 At <mark>las</mark> -Mini Slimline Floodlight in White			10W	760lm	900lm	110°	130mm	140mm	30mm	
6416 At <mark>las</mark> -Mini Slimline Floodlight in Black			20W	1450lm	1600lm	110°	193mm	201mm	34mm	
10338 Atlas-Mini Slimline Floodlight in White			20W	1450lm	1600lm	110°	193mm	201mm	34mm	
6430 Atlas-Mini Slimline Floodlight in Black			30W	2200lm	2400lm	110°	193mm	201mm	a 34mm	
10352 Atlas-Mi	0352 Atlas-Mini Slimline Floodlight in White			2200lm	2400lm	110°	193mm	201mm	nm 34mm	
6454 Atlas-Mi	6454 Atlas-Mini Slimline Floodlight in Black			3850lm	4200lm	110°	285mm	298mm	28mm 40mm	
10376 Atlas-Mini Slimline Floodlight in White			50W	3850lm	4200lm	110°	285mm	298mm 40mm		
Atlas Mini Slimline floodlight - WITH PIR										
7598 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in Black	10W	760lm	900lm	110°	188mm	140mm	51mm	
10321 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in White	10W	760lm	900lm	110°	188mm	140mm	51mm	
6423 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in Black	20W	1450lm	1600lm	110°	229mm	201mm	51mm	
10345 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in White	20W	1450lm	1600lm	110°	229mm	201mm	51mm	
6447 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in Black	30W	2200lm	2400lm	110°	229mm	201mm	51mm	
10369 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in White	30W	2200lm	2400lm	110°	229mm	201mm	51mm	
6461 Atlas-Mi	ni Slimline Floodlight	with PIR Sensor in Black	50W	3850lm	4200lm	110°	285mm	298mm	55mm	
10383 Atlas-Mini Slimline Floodlight with PIR Sensor in White			50W	3850lm	4200lm	110°	285mm	298mm	55mm	
*Extra core becomes live when PIR activated which allows for multiple fittings to be controled by one PIR. (6423 ONLY)										

Lighting brilliance since 1878